

GammaTRACER Spider

Gamma Probe for Emergency Response



OVERVIEW

The autonomous **GammaTRACER Spider** gamma probe is specially designed to cover the needs of first responders in an emergency scenario.

Based on the proven GammaTRACER design, the probe provides reliable measurement of the gamma dose rate and wireless data transmission to the crisis center by using SkyLINK/ShortLINK radio or Iridium satellite modem.

The compact design and innovative self-erecting enclosure facilitate deployment and minimize time, particularly important for emergency use and roll-out in contaminated area. The probe can simply be dropped out of a vehicle or pushed out through a lock or outlet. Thus, exposure to personnel can be significantly reduced. Alternatively deployment by a remote controlled drone or by parachute is possible.

Due to its excellent reception performance, SkyLINK radio provides outstanding area coverage independent from public communication networks, proven in many installations worldwide. Alternatively, data transmission by Iridium satellite can be suitable wherever very large areas have to be covered. As public telecom infrastructure might be affected by overload or wide-ranging power breakdown, GammaTRACER is THE solution for emergency applications.

BENEFITS

- Ultra compact self-erecting design, very simple deployment
- Maximum protection of first responders
- Emergency proof communication options
- SkyLINK/ShortLINK radio (up to 100 km / 60 mi) or satellite modem (Iridium)
- Rechargeable battery, up to 4 year's operation
- Built-in GPS
- Hermetically sealed weatherproof housing
- 2 uR/h up to 1,000 R/h
- Allows fast extension of monitoring network
- Quick and simple to use, from field operator to scientist



GammaTRACER Spider

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Measurement range	2 uR/h - 100 R/h (20 nSv/h ... 1 Sv/h) Optional 1,000 R/h (10 Sv/h)
Measurement cycle	1 min - 2 hours
Internal data storage	Up to 12 000 data sets
Detector	GM tube
Additional Sensors	GPS, temperature, motion

ENVIRONMENTAL CHARACTERISTICS

Temperature range	-4° F - 122° F (-20°C - +50°C), optional -22°F - 140°F (-30° C - 60° C)
Humidity	100%
Protection class	IP 68 (hermetically sealed)

PHYSICAL DIMENSIONS

Dimensions	4.3" W x 25.6" H (110 mm W x 650 mm H)
Weight	5.5 lb (2.5 kg)

POWER

Power	Built-in rechargeable battery pack, easy exchange in the field
Battery Life	4 years without data transmission (GPS once/day) 3 months with SkyLINK/ShortLINK radio @ 1 min cycle / 1 min Tx 2 years with SkyLINK/ShortLINK radio @ 10 min cycle / 10 min Tx 3 years with SkyLINK/ShortLINK radio @ 1h cycle / 1h Tx 1 year with satellite, Iridium modem @ 10 min cycle / 1 h Tx 2.5 years with satellite, Iridium modem @ 1h cycle / 4 h Tx

COMM INTERFACES

Local port	Infrared interface for data readout and setup
Option	Built-in SkyLINK/ShortLINK radio modem for data transmission up to 100 km / 60 mi (SkyLINK), 5 km / 3 mi (ShortLINK), depending on site conditions
Option	Built-in Iridium satellite modem, worldwide coverage

DataEXPERT DATA MANAGEMENT SOFTWARE

- Automatic processing of measurement data from different instruments (monitors for gamma, aerosols, spectroscopy, iodine, gas)
- Alarm management, event notification by email / SMS
- Visualization of current and historic data on static or GIS maps
- NEW: WebVIEW module for data visualization by web browser
- MS-SQL database
- Various report and export functions
- Option: Redundant server topology for high availability requirements

