

# RDS 30

## Radiation Survey Meter



### RDS-30

The RDS-30 is a Digital Handheld Dose Rate Meter designed for a wide range of applications involving a possibility for abnormal radiation levels. Compact, lightweight, waterproof, its performance and its friendly user interface make the RDS-30 perfectly suited to radiation survey in field conditions, in nuclear industry and for protection against radiological hazards by personnel, who may be exposed to gamma and/or X-ray radiation in their work.

RDS-30 is microprocessor controlled. The user interface consists of one push button and an easy- to-use menu structure that displays information on the LCD of the meter. The six-digit display shows the dose rate and various messages. Different alarm situations are indicated by a combination of audio-visual effects on the LCD and a buzzer (dose rate , dose, low battery, defect, dose rate overflow).

RDS-30 provides user configurable (with RDS-CSW SW) list of alarm levels for dose and dose rate. Fixed or multilevel alarm options. It is possible to store dose rate values into the histogram memory for later analysis of the readings.

The use of a RDS-CSW software is required for downloading the data into a PC via IrDA port.

### FEATURES

- Small size and large display
- Measurement in  $\mu\text{Sv/h}$  or  $\text{mrem/h}$
- Gamma dose indication
- Visual and audible signalling
- High battery life time (>1 year)
- Compliant to IEC 60846
- Dose rate follow-up by audible signal with frequency proportional to dose rate
- Visual and audible alarm: user settable for dose and dose rate over the whole measurement range
- Histogram capability of up to 480 dose rate values with user settable logging interval
- Backlit display with six large digits
- Display in either  $\text{mrem/h}$  or  $\mu\text{Sv/h}$
- Built-in self-diagnostics complies with ANSI N42.33 and IEC 60846 standards

# RDS 30

## TECHNICAL SPECIFICATIONS:

### Radiological characteristics

- Radiation detected: gamma and X-ray from 48 keV to 1.3 MeV
- Detector: energy compensated GM tube compliant to H\*(10)
- Dose rate measurement range: 1  $\mu$ rem/h to 10 rem/h (0.01  $\mu$ Sv/h to 100 mSv/h)
- Dose rate linearity:  $\pm 10\%$   $\pm 10$   $\mu$ rem/h to 10 rem/h (0.1  $\mu$ Sv/h to 100 mSv/h or 10  $\mu$ rem/h)
- Calibration accuracy:  $\pm 5\%$  of the reading in <sup>137</sup>Cs exposure, at 3 mSv/h, 68°F (+20°C)
- Energy response:  $\pm 30\%$  over the range of 48 keV - 1.3 MeV
- Angular response:  $\pm 25\%$  within  $\pm 45^\circ$  from the calibration direction at 48 keV
- Dose measurement range: 1  $\mu$ rem to 100 rem (0.01  $\mu$ Sv to 1 Sv)

### Functional characteristics

- Dose rate follow-up by audible signal with frequency proportional to dose rate
- Visual and audible alarm: user settable for dose and dose rate over the whole measurement range
- Dose measurement (mRem /  $\mu$ Sv)
- Histogram capability of up to 480 dose rate values with user settable logging interval
- Backlit display with six large digits
- Display in either mRem/Hr or  $\mu$ Sv/h (configurable per request)
- Built-in self diagnostics for GM-tube operation, high voltage and battery capacity
- Built-in infra-red port (IrDA)

### Mechanical characteristics

- Case: rugged plastic, easily decontaminable
- Dimensions: 3.07 x 4.96 x 1.25 in (78 x 126 x 32 mm)
- Weight: 6.0 oz (170 g) without batteries, 7.76 oz (220 g) with batteries

### Environmental Characteristics

- Temperature range : -13 - +131°F (-25 - +55°C) operational, -40 - +158°F (-40 - +70°C) storage
- Protection level: IP67 (temporary immersion / floating device)

### Electrical Characteristics

- Power supply: 2 alkaline batteries leC LR6/AA size (recommended)
- Battery life time: at least 2000 hours at normal background with alkaline cells (more than 1 year under normal operation)
- Battery alarm: two-step alarm for low battery voltage
- Electromagnetic compatibility: CE compliant

### Accessories

- RDS-CSW software for parameter setting and histogram readings ( can be downloaded free of charge at [www.mirion.com](http://www.mirion.com), requires an USB-IrDA adapter)
- CSW Configuration SW full version with calibration key
- Wrist strap
- Neck strap



USB-IrDA adapter

