

CP-100 and BG-300 Radioiodine Samplers



The RADeCO™ Models CP-100 and BG-300 Radioiodine Samplers are special sampling cartridges specifically designed for the evaluation of airborne concentrations of elemental radioiodine, organic radionuclides, and other radioiodine compounds. They are composed of selected 5% TEDA treated charcoal packaged in a plastic case.

Each batch of Model CP-100 and BG-300 cartridges is manufactured from pre-tested charcoal. After loading the material into the cartridges, random sample cartridges are selected and subjected to stringent radioiodine testing procedures. An independent laboratory develops a Certificate of Performance assuring the user of the quality of the product. This certificate is included with each purchase.

The Model CP-100 Radioiodine Sampler utilizes 40x50 mesh charcoal and is designed for very high collection efficiency at high flow rates for long term sampling. The Model BG-300 Radioiodine Sampler uses 20x 30 mesh charcoal and is designed for use at low flow sampling operations.

These cartridges are routinely used in-line and downstream of a high efficiency filter which will remove radioactive particulates which can interfere with the radioiodine measurement. Filter papers and combination pre-filter and cartridge sample holders are available as accessories for the RADeCO air samplers.

CAUTION: Models CP-100 and BG-300 Radioiodine Samplers must not be used in personal respirators for breathing protection.

CP-100 GENERAL FEATURES

- 2.27" Diameter X 1.04" Thick
- 40x50 mesh TEDA treated charcoal
- Plastic case**
- Uniform loading and density packed
- Certified for Performance
- Percent retention vs. flow rate

- ### BG-300 GENERAL FEATURES
- 2.27" Diameter X 1.04" Thick
 - 20x30 mesh TEDA treated charcoal
 - Plastic case**
 - Uniform loading and density packed
 - Certified for Performance
 - Percent retention vs. flow rate

CP-100 and BG-300 Radioiodine Samplers

TYPICAL CARTRIDGE DATA - CP-100

Flow Rate CFM (LPM)	Retention* 18 hour Purge	Retention* 7 day Purge	? P Across Cartridge Inches
1 (28)	99	99	.47
3 (85)	97	97	1.8
4 (113)	95	94	2.5
5 (142)	93	93	3.3
6 (130)	91	89	4.0
7 (198)	89	87	5.0

TYPICAL CARTRIDGE DATA - BG-300

Flow Rate CFM (LPM)	Retention* 18 hour Purge	Retention* 7 day Purge	? P Across Cartridge Inches
1 (28)	99	99	.18
2 (57)	96	96	.45
3 (85)	92	92	.83
4 (113)	85	85	1.55
5 (142)	82	81	2.15

*Rounded to whole % -These collection efficiencies may vary slightly from batch to batch.

Testing - RADēCO™ cartridges are tested by an outside independent laboratory. Twenty-five (25) separate test measurements (or more) are utilized to produce our Certificate of Performance. These tests certify the retention efficiencies of methyl iodide at 30 C and 95% RH in accordance with ASTM D-3803-89, Sect 12

Calibration Material - Methyl Iodide—This is the most difficult of the organic iodides to collect for analysis. The collection efficiency for other radionuclides will be higher.

Storage Life - The CP-100 and BG-300 cartridges are packed in sleeves of 20 cartridges each. Each sleeve is of 10 mil plastic with the ends heat-sealed. The shelf life for each cartridge is 10 years from date of manufacturer. This information should be on the label. Special individual cartridge packaging is available.

** Certified Incinerable

